



## Normally-On Trench Silicon Carbide Power JFET

Product Summary		
$BV_{DS}$	650	V
$R_{DS(on)max}$	0.055	$\Omega$

### Features:

- Positive Temperature Coefficient for Ease of Paralleling
- Extremely Fast Switching with No "Tail" Current at 150 °C
- $R_{DS(on)max}$  of 0.055  $\Omega$
- Voltage Controlled
- Low Gate Charge
- Low Intrinsic Capacitance



Internal Schematic

### Applications:

- Solar Inverter
- SMPS
- Power Factor Correction
- Induction Heating
- UPS
- Motor Drive

## MAXIMUM RATINGS

Parameter	Symbol	Conditions	Value	Unit
Continuous Drain Current	$I_{D, TC=25}$	$T_C = 25\text{ }^\circ\text{C}$	30	A
	$I_{D, TC=100}$	$T_C = 100\text{ }^\circ\text{C}$	20	
Pulsed Drain Current <sup>(1)</sup>	$I_{DM}$	$T_j = 25\text{ }^\circ\text{C}$	80	A
Short Circuit Withstand Time	$t_{SC}$	$V_{DD} < 800\text{ V}, T_C < 125\text{ }^\circ\text{C}$	50	$\mu\text{s}$
Power Dissipation	$P_D$	$T_C = 25\text{ }^\circ\text{C}$	114	W
Gate-Source Voltage	$V_{GS}$	AC <sup>(2)</sup>	-15 to +15	V
Operating and Storage Temperature	$T_j, T_{stg}$		-55 to +150	$^\circ\text{C}$
Lead Temperature for Soldering	$T_{sold}$	1/8" from case < 10 s	260	$^\circ\text{C}$

<sup>(1)</sup> Pulse width limited by maximum junction temperature

<sup>(2)</sup>  $R_{g(EXT)} = 1\text{ } \Omega, t_p \leq 200\text{ ns}$ , see Figure 6 for static conditions

## THERMAL CHARACTERISTICS

Parameter	Symbol	Value		Unit
		Typ	Max	
Thermal Resistance, junction-to-case	$R_{th,JC}$	-	1.1	$^\circ\text{C} / \text{W}$
Thermal Resistance, junction-to-ambient	$R_{th,JA}$	-	50	

### ELECTRICAL CHARACTERISTICS

Parameter	Symbol	Conditions	Value			Unit
			Min	Typ	Max	

#### Off Characteristics

Drain-Source Blocking Voltage	$BV_{DS}$	$V_{GS} = -15\text{ V}, I_D = 600\ \mu\text{A}$	650	-	-	V
Total Drain Leakage Current	$I_{DSS}$	$V_{DS} = 650\text{ V}, V_{GS} = -15\text{ V}, T_j = 25\text{ }^\circ\text{C}$	-	10	-	$\mu\text{A}$
		$V_{DS} = 1200\text{ V}, V_{GS} = -15\text{ V}, T_j = 150\text{ }^\circ\text{C}$	-	100	-	
Total Gate Reverse Leakage	$I_{GSS}$	$V_{GS} = -15\text{ V}, V_{DS} = 0\text{ V}$	-	0.1	0.3	mA
		$V_{GS} = -15\text{ V}, V_{DS} = 650\text{ V}$	-	0.1	-	

#### On Characteristics

Drain-Source On-resistance	$R_{DS(on)}$	$I_D = 20\text{ A}, V_{GS} = 2\text{ V}, T_j = 25\text{ }^\circ\text{C}$	-	0.050	0.055	$\Omega$
		$I_D = 20\text{ A}, V_{GS} = 2\text{ V}, T_j = 100\text{ }^\circ\text{C}$	-	0.07	-	
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = 1\text{ V}, I_D = 30\text{ mA}$	-	-5	-	V
Gate Forward Current	$I_{GFWD}$	$V_{GS} = 2\text{ V}$	-	23	-	$\mu\text{A}$
Gate Resistance	$R_G$	$f = 1\text{ MHz}, \text{ drain-source shorted}$	-	6	-	$\Omega$

#### Dynamic Characteristics


Input Capacitance	$C_{iss}$	$V_{DD} = 100\text{ V}, V_{GS} = -15\text{ V}, f = 100\text{ kHz}$	-	470	-	$\text{pF}$
Output Capacitance	$C_{oss}$		-	130	-	
Reverse Transfer Capacitance	$C_{rss}$		-	120	-	
Effective Output Capacitance, energy related	$C_{o(er)}$	$V_{DS} = 0\text{ V to } 400\text{ V}, V_{GS} = -15\text{ V}$	-	90	-	

#### Switching Characteristics

Turn-on Delay	$t_{on}$	$V_{DS} = 325\text{ V}, I_D = 20\text{ A}, \text{ Inductive Load}, T_j = 25\text{ }^\circ\text{C}$ Gate Driver = +15 V, -15 V, $R_{g(EXT)} = 1\ \Omega$	-	10	-	ns
Rise Time	$t_r$		-	20	-	
Turn-off Delay	$t_{off}$		-	20	-	
Fall Time	$t_f$		-	16	-	
Turn-on Energy	$E_{on}$		-	56	-	
Turn-off Energy	$E_{off}$	See Figure 13	-	63	-	$\mu\text{J}$
Total Switching Energy	$E_{ts}$	-	119	-		
Turn-on Delay	$t_{on}$	$V_{DS} = 325\text{ V}, I_D = 20\text{ A}, \text{ Inductive Load}, T_j = 150\text{ }^\circ\text{C}$ Gate Driver = +15 V, -15 V, $R_{g(EXT)} = 1\ \Omega$	-	TBD	-	
Rise Time	$t_r$		-	TBD	-	
Turn-off Delay	$t_{off}$		-	TBD	-	
Fall Time	$t_f$		-	TBD	-	
Turn-on Energy	$E_{on}$		-	TBD	-	
Turn-off Energy	$E_{off}$	See Figure 13	-	TBD	-	$\mu\text{J}$
Total Switching Energy	$E_{ts}$	-	TBD	-		
Total Gate Charge	$Q_g$	$V_{DS} = 400\text{ V}, I_D = 20\text{ A}$ $V_{GS} = -15\text{ V to } +2\text{ V}$	-	70	-	
Gate-Source Charge	$Q_{gs}$		-	6	-	
Gate-Drain Charge	$Q_{gd}$		-	48	-	


**Figure 1. Typical Output Characteristics**

$I_D = f(V_{DS}); T_j = 25\text{ }^\circ\text{C}; \text{parameter: } V_{GS}$




**Figure 2. Typical Output Characteristics**

$I_D = f(V_{DS}); T_j = 100\text{ }^\circ\text{C}; \text{parameter: } V_{GS}$




**Figure 3. Typical Output Characteristics**

$I_D = f(V_{DS}); T_j = 150\text{ }^\circ\text{C}; \text{parameter: } V_{GS}$




**Figure 4. Safe Operating Area**

$I_D = f(V_{DS}); T_C = 25\text{ }^\circ\text{C}$




**Figure 5. Typical Transfer Characteristics**

$I_D = f(V_{GS}); V_{DS} = 5\text{ V}; T_j = 25\text{ }^\circ\text{C}$




**Figure 6. Gate Current**

$I_G = f(V_{GS}); \text{parameter: } T_j$




**Figure 7. Drain-Source On-resistance**

$$R_{DS(on)} = f(I_D); V_{GS} = 2.0 \text{ V}; \text{ parameter: } T_j$$




**Figure 8. Drain-Source On-resistance**

$$R_{DS(ON)} = f(T_j); I_D = 20 \text{ A}; \text{ parameter: } V_{GS}$$




**Figure 9. Drain-Source On-resistance**

$$R_{DS(on)} = f(V_{GS}); I_D = 20 \text{ A}; T_j = 25^{\circ}\text{C}$$




**Figure 10. Typical Capacitance**

$$C = f(V_{DS}); V_{GS} = -15 \text{ V}; f = 100 \text{ kHz}$$




**Figure 11. Gate Charge**

$$Q_g = f(V_{GS}); V_{DS} = 400 \text{ V}; I_D = 20 \text{ A}; T_j = 25^{\circ}\text{C}$$




**Figure 12. Drain-Source Leakage**

$$I_{DSS} = f(V_{DS}); V_{GS} = -15 \text{ V}; \text{ parameter: } T_j$$







**Figure 13. Switching Energy Losses**

$E_s = f(I_D)$ ;  $V_{DS} = 325\text{ V}$ ;  $GD = +15\text{ V}/-15\text{ V}$ ,  $R_{GEXT} = 1\ \Omega$



**Figure 14. Inductive Load Switching Circuit**





DIM	MILLIMETERS		INCHES	
	MIN	MAX	MIN	MAX
A	4.191	4.699	0.165	0.185
A1	2.387	2.489	0.094	0.098
A2	1.219	1.321	0.048	0.052
b	0.635	0.889	0.025	0.035
b1	1.143	1.397	0.145	0.055
c	0.458	0.635	0.018	0.025
D	15.113	16.621	0.595	0.615
D1	9.017	9.271	0.355	0.365
e	2.540		0.100	
E	9.677	9.931	0.381	0.391
L	12.700	12.954	0.500	0.510
L1	3.048	3.302	0.120	0.130
Q	2.540	3.048	0.100	0.120
ØP	3.632	3.734	0.143	0.147

Published by  
SemiSouth Laboratories, Inc.  
201 Research Boulevard  
Starkville, MS 39759 USA  
© SemiSouth Laboratories, Inc. 2012

Information in this document supersedes and replaces all information previously supplied.

Information in this document is provided solely in connection with SemiSouth products. SemiSouth Laboratories, Inc. reserves the right to make changes, corrections, modifications or improvements, to this document without notice.

No license, express or implied to any intellectual property rights is granted under this document.

Unless expressly approved in writing by an authorized representative of SemiSouth, SemiSouth products are not designed, authorized or warranted for use in military, aircraft, space, life saving, or life sustaining applications, nor in products or systems where failure or malfunction may result in personal injury, death, or property or environmental damage.